



## AT-2750FX

### Fast Ethernet Secure Fiber Interface Card

#### AT-2750FX/xx

100FX 32-bit, PCI 2.2 compliant secure fiber interface card

#### Secure Fiber Network Interface Card

The AT-2750FX secure interface card hardens at-risk systems without impacting performance. It features an embedded security processor to offload encryption, authentication, and other cycle-intensive tasks from the host CPU—resulting in optimal system and application response. The types of encryption supported are DES, 3DES, FIPS capable (not certified) and AES (upon Vista release - pending).

#### Encryption

**DES:** The Data Encryption Standard (DES) is a 56-bit key method for encrypting information selected as an official Federal Information Processing Standard (FIPS) for the United States in 1976.

**3DES:** The Triple Data Encryption Standard (3DES) is the successor of DES, and uses a 168-bit sized key. 3DES is very secure.

**AES:** Advanced Encryption Standard (AES) is a block cipher adopted as an encryption standard by the US government. It has been analyzed extensively and is now used widely worldwide. AES was announced by the National Institute of Standards and Technology (NIST) as US FIPS PUB 197 (FIPS 197) and became a standard in May 26, 2002.

**FIPS:** The Federal Information Processing Standard 140 (FIPS) are a series of US government computer security standards that specify requirements for cryptography modules.

#### Key Features

##### Advance Properties

- Secured transmission
- PCI 2.2 capable
- Low profile and standard height brackets included
- RoHS compliant
- 3DES
- AES
- IPv6
- Compliant with Trade Agreement Act

# AT-2750FX | Fast Ethernet Secure Fiber Interface Card

## Specifications

### Bus Type

PCI 2.2

### Ethernet Standards

IEEE 802.2	LLC
IEEE 802.3ac	MAC
IEEE 802.3u	Fast Ethernet

### Drivers

#### Supported

Windows XP

### Compliance

UL  
FCC/EN55022 Class B  
TUV  
EN55024  
CE

### Environmental Specifications

Operating temperature	0°C to 50°C
Storage temperature	-25°C to 70°C
Relative humidity	5% to 90% non-condensing

### Power

Power consumption	4.8 Watts (max)
Signaling voltage	3.3/5V

### Status Indicators

LED	1 port	
Link/ACT	On	Link activity
	Blink	Activity
FDX	On	Full-duplex mode
	Off	Half-duplex mode

### Physical Characteristics

Dimensions	16.8cm x 6.9cm
(W x H)	(6.7") x (2.7")
Weight	0.34lb (0.15kg)

Ships with standard bracket attached to interface card.  
Low-profile bracket is included in packaging.

### Connectors/Interface

SC  
ST  
Optical receive sensitivity (max) -31dBm  
Transmit optical power (min/max) -19/-14dBm

## Ordering Information

### AT-2750FX/xx

100FX 32-bit, PCI 2.2 compliant secure fiber interface card

Where xx = ST, SC

Ships with standard bracket attached to interface card.  
Low-profile bracket is included in packaging.

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesis.com](http://www.alliedtelesis.com)

© 2007 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000236 Rev. C