



*The CentreCOM
AT-MX40F/ST, AT-MX50F/SM, AT-MX55F/SC
Micro Ethernet Transceiver Installation Guide*

Overview

Allied Telesyn supports all common Ethernet media with Micro Transceivers for thin coax (10BASE2), UTP (10BASE-T) and fiber optic (10BASE-FL, FOIRL) LAN systems. The transceivers support a single AUI that attaches directly to the AUI 15-pin connection found on most Ethernet stations (DTEs).

Preparation

An SQE Test switch is available to provide IEEE 802.3 Ethernet SQE Testing. Allied Telesyn ships transceivers with the SQE Test/heartbeat disabled as the default. Before you install the product, consult your DTE's documentation to determine if you need to enable or disable this function.

Installation

1. Install the AT-MX40F/ST, AT-MX50F/SM, or AT-MX55F/SC Micro Ethernet Transceiver directly to the DTE or workstation AUI port. If you use an AUI drop cable, make sure it is not longer than 50m (164 ft.).
2. Select SQE Test /Heartbeat function ON or OFF depending on the DTE requirements.
3. Disable the SQE Test function if a transceiver is connected to an Ethernet repeater.
4. Connect the fiber optic cable connectors to the ST, SM, or SC type of installed transceiver.

NOTE

Ensure that the Transmit connector on one side of fiber optic cable goes to the Receive connector on the fiber optic device at the opposite end of the link.

Maximum fiber optic links permissible are 2000m (6556 ft.) 10BASE-FL or 1000m (3278 ft.) FOIRL.

LED Explanation

The AT-MX40F/ST, AT-MX50F/SM, and the AT-MX55F/SC provide diagnostic and status information, as shown in the following LED table.

Table 1: LED Guide

LED Name	Meaning When LED Is Lighted
PWR	Indicates power is applied
TX	Indicates data is transmitted
LNK	Indicates link is established
RX	Indicates data is received
COL	Indicates a collision is detected
JBR	Identifies failed logic or circuits

RADIATED ENERGY

Declaration Of Conformity

Complies with FCC Part 15B, Class B Limits:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device must not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with instructions, may cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes and modifications not expressly approved by the manufacturer or registrant of this equipment can void your authority to operate this equipment under Federal Communications Commission rules.

Canadian Department of Communications

This Class B digital apparatus meets all requirements of the Canadian Interference-Causing Equipment Regulations.
Cet appareil numérique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

STANDARDS: This product meets the following standards

RFI Emission	EN55022 Class B
Immunity	EN50082-1
Electrical Safety	EN60950, UL1950, CSA 950

SAFETY

LIGHTNING DANGER

DANGER: DO NOT WORK on equipment or CABLES during periods of LIGHTNING ACTIVITY.

Operating temperature

This product is designed for a maximum ambient temperature of 40 degrees C.

Environmental Air Notice

CAUTION: UL listed for use in other Environmental Air Spaces in Accordance with Article 300-22(C) of the U.S.A National Electrical Code. Note: Product is not Plenum rated.

This is a "CLASS 1 LED PRODUCT."

All Countries: Install product in accordance with local and National Electrical Codes.

NORMEN: Dieses Produkt erfüllt die Anforderungen der nachfolgenden Normen.

Hochfrequenzstörung	EN55022 Klasse B
Störsicherheit	EN50082-1
Elektrische Sicherheit	EN60950, UL1950, CSA 950

SIKERHED

GEFAHR DURCH BLITZSCHLAG

GEFAHR: Keine Arbeiten am Gerät oder an den Kabeln während eines Gewitters ausführen.

BETRIEBSTEMPERATUR

Dieses Produkt wurde für den Betrieb in einer Umgebungstemperatur von nicht mehr als 40° C entworfen.

Das ist ein "LED Produkt der Klasse 1."

Alle Länder: Installation muß örtlichen und nationalen elektrischen Vorschriften entsprechen.

SIKKERHED

FARE UNDER UVEJR

FARE: UNDLAD at arbejde på udstyr eller KABLER i perioder med LYNAKTIVITET.

BETJENINGSTEMPERATUR

Dette apparat er konstrueret til en omgivende temperatur på maksimum 40 grader C.

Dette er et "Produkt under Klasse 1 LED."

Alle Lande: Installation af produktet skal ske i overensstemmelse med lokal og national lovgivning for elektriske installationer.

VEILIGHEID

GEVAAR VOOR BLIKSEMINSLAG

GEVAAR: NIET aan toestellen of KABELS WERKEN bij BLIKSEM.

Bedrijfstemperatuur:

De omgevings temperatuur voor dit product mag niet meer bedragen dan 40 graden Celsius.

Dit is een "Klasse 1 LED-product."

Alle landen: het toestel installeren overeenkomstig de lokale en nationale elektrische voorschriften.

NORMES: ce produit est conforme aux normes de suivantes:

Emission d'interférences radioélectriques	EN55022 Classe B
Immunité	EN50082 - 1
Sécurité électrique	EN60950, UL1950, CSA 950

SECURITE



DANGER DE Foudre
DANGER: NE PAS MANIER l'équipement ou les CABLES pendant les périodes d'activité orageuse.



TEMPERATURE DE FONCTIONNEMENT
Ce produit est capable de tolérer une température ambiante maximum de 40 degrés Celsius.
Ce produit est un « **Produit à diode électroluminescente de classe 1.** »
Pour tous pays: Installer le produit conformément aux normes électriques nationales et locales.



TURVALLISUUS

SALAMANISKUAARA
HENGENVAARA: ÄLÄ TYÖSKENTELE laitteiden tai KAAPELIDEN KANSSA SALAMOINNIN AIKANA.



KÄYTTÖLÄMPÖTILA
Tämä tuote on suunniteltu ympäröivän ilman maksimilämpötilalle 40°C.
Tämä on "ensimmäisen luokan valodiodituote."



Kaikki maat: Asenna tuote paikallisten ja kansallisten sähköturvallisuusmääräysten mukaisesti.



NORME DI SICUREZZA

PERICOLO DI FULMINI
PERICOLO: NON LAVORARE sul dispositivo o sui CAVI durante PRECIPITAZIONI TEMPORALESCHIE.



Temperatura di funzionamento
Questo prodotto è concepito per una temperatura ambientale massima di 40 gradi centigradi.
Questo è un "Prodotto con LED di Classe I."



Tutti i paesi: installare il prodotto in conformità alle vigenti normative elettriche nazionali.



SIKKERHET

FARE FOR LYNANTENNELSE
FARE: MÅ IKKE BRUKES på utstyr eller ledninger mens LYN-AKTIVITET er i gang.



Driftstemperatur
Dette produktet har blitt fremslått til bruk med maksimum romtemperatur på 40 grader celsius.
Dette er et "Klasse en LED produkt."



Alle land: Produktet må installeres i samsvar med de lokale og nasjonale elektriske koder.



SEGURANÇA

PERIGO DE CHOQUE CAUSADO POR RAI
PERIGO: NÃO TRABALHE no equipamento ou nos CABOS durante períodos suscetíveis de QUEDAS DE RAI.



TEMPERATURA DE FUNCIONAMENTO
Este produto foi projetado para uma temperatura ambiente máxima de 40 graus centígrados.
Este é um "Produto Classe 1 LED."



Todos os países: Instale o produto de acordo com as normas federais e locais para instalações elétricas.



SEGURIDAD

PELIGRO DE RAYOS
PELIGRO: NO REALICE NINGUN TIPO DE TRABAJO O CONEXION en los equipos o en LOS CABLES durante TORMENTAS DE RAYOS.



Temperatura requerida para la operación
Este producto está diseñado para una temperatura ambiental máxima de 40 grados C.



Para todos los países: Monte el producto de acuerdo con los Códigos Eléctricos locales y nacionales.



SÄKERHET

FARA FÖR BLIXTNEDSLAG
FARA: ARBETA EJ på utrustningen eller kablarna vid ÅSKVADER.



DRIFTSTEMPERATUR
Denna produkt är konstruerad för rumstemperatur ej överstigande 40 grader Celsius.
Detta är en "Klass 1 lysdiodprodukt."



Alla länder: Installera produkten i enlighet med lokala och statliga bestämmelser för elektrisk utrustning.

For more information on Allied Telesyn products available today and in the future, contact your local Allied Telesyn representative:

Office:	USA	Germany	U.K.
Phone:	1 (800) 428-4835	(+49) 30-435-900126	(+44) 1-235-442560
Fax:	1 (425) 481-3790	(+49) 30-432-70650	(+44) 1-235-442490

Office:	France	Japan	Asia
Phone:	(+33) 1-60-92-15-32	(+81) 3-3443-5640	(+65) 3815-613
Fax:	(+33) 1-69-28-37-49	(+81) 3-3443-2443	(+65) 3833-830





Allied Telesyn International
19015 North Creek Parkway
Bothell, WA 98011 USA
Tel (425) 487-8880 • Fax (425) 489-9191
Technical Support Tel (800) 428-4835 • Fax (425) 481-3790

PN 613-10380-00 Rev. C

980327