

# CentreCOM<sup>®</sup> GS900M Copper Series

## Layer 2 Gigabit Access Switches

Allied Telesis CentreCOM GS900M Series copper Gigabit access switches are cost-effective and fully managed. GS900M Series switches deliver flexible uplink connectivity with one small form-factor pluggable (SFP) slot on the 8-port model and 2 or 4 unpopulated combo ports (10/100/1000T or 100FX/1000X) on the 16/24-port models.



### Overview

CentreCOM GS900M Series switches feature quiet operation with a compact, fanless 8-port model and a variable fan control feature on the 16/24-port models. All models feature 0-50°C extended temperature capability. In addition, the CentreCOM GS900M Series includes ECO LED, ECO Trigger, and Power Saving Mode for energy efficiency. CentreCOM GS900M Series switches provide an intelligent, energy efficient, and cost-effective solution for the edge of the network.

### Key Features

- ▶ Web-based graphical user interface for simplified administration
- ▶ Supports up to 50°C extended temperature
- ▶ Eco-friendly
- ▶ Flexible LAN authentication functions
- ▶ Tri Authentication: Any one physical port can support a combination of IEEE 802.1X, MAC, and Web Authentication. Therefore, the user doesn't have to set each port configuration based on the authentication method on the connected device
- ▶ Multiple Dynamic VLAN: The traffic from a device is classified into a dynamic VLAN after the connection is authenticated
- ▶ IGMP v3 / MLD v2 Snooping: Limits the flooding of multicast traffic by dynamically configuring L2 interfaces so that multicast traffic is forwarded to only those interfaces associated with IP multicast address

### Specifications

#### Port Speed

10Mbps/100Mbps/1000Mbps

#### Port Configuration

Ports	10/100/1000T (RJ-45 Connector)
	AT-GS908M × 8
	AT-GS916M × 16
	AT-GS924M × 24
Auto-Negotiation	
Auto MDI/MDI-X	
MDI/MDI-X Manual Configuration	
Full Duplex/Half Duplex Manual Configuration (only on 10/100Mbps mode)	
SFP Slots	AT-GS908M × 1 AT-GS916M × 2 AT-GS924M × 4

#### Cable Specifications

10T	UTP Category 3 or better
100T	UTP Category 5 or better
1000T	UTP Enhanced Category 5 or better

#### Ethernet Specifications

IEEE 802.3	10BASE-T
IEEE 802.3u	100BASE-TX
IEEE 802.3u	100BASE-FX
IEEE 802.3ab	1000BASE-T
IEEE 802.3z	1000BASE-SX/LX
IEEE 802.3ah	1000BASE-BX, 1000BASE-BX10
IEEE 802.3x	Flow Control
IEEE 802.3ad	Link Aggregation Manual Configuration
IEEE 802.1D	Spanning-Tree STP Compatible
IEEE 802.1Q	VLAN Tagging
IEEE 802.1X	Port-Based Network Access Control
IEEE 802.1p	Class of Service, priority protocol
IEEE 802.1s	Multiple Spanning-Tree
IEEE 802.1w	Rapid Spanning-Tree

#### LEDs

Selectable Port LED as Speed or Duplex indicator, port LED can be disabled.	
LINK/ACT	Green: Link Established Flashing: Send/Receive Packets
SPD/DPX (SPEED)	Green: 1000Mbps link established
SPD/DPX (DUPLEX)	Green: Full Duplex link established
SFP Slot LED	
LINK/ACT	Green: Link Established Flashing: Send/Receive Packets
Status LED	
POWER	Green: Power On

FAULT

Red: Detecting Error  
Flashing: Booting, Writing to Flash  
Memory, Error on FAN, Voltage, Temp  
Green: Standby Mode

STANDBY

### Supported Features

VLAN (Port-based/IEEE 802.1Q Tagging)  
Multiple VLAN  
Spanning-Tree (IEEE 802.1 D STP Compatible/IEEE 802.1 w/ IEEE 802.1s)  
QoS (IEEE 802.1p/Diffserv)  
Policy-Based QoS  
IEEE 802.1x Authentication (Single Host/Multiple Host/ Multiple Authentication)  
IEEE 802.1x Encryption Mode (MD5/TLS/TTLs/PEAP)  
Dynamic VLAN  
Multiple Dynamic VLAN  
MAC Address-based Authentication  
Web Authentication  
Supplicant MAC Authentication  
EPSR-Aware  
Port Trunking (IEEE 802.3ad Manual Configuration)  
Port Mirroring  
Port Security  
Flow Control  
Packet Storm Protection  
Loop Guard (LDF Detection/Ingress Rate Detection)  
Ingress Filtering  
HoL Blocking Prevention  
IGMP v3 Snooping  
MLD v2 Snooping  
BPDU/EAP Forwarding  
DHCP Snooping  
Access Filter  
DHCP Client  
RADIUS Accounting  
Jumbo Frame  
Logging  
Script  
SNTP  
Statistics  
eco-friendly features (Power Saving Mode)  
Auto Fan Control  
Download firmware and configuration by TFTP/Zmodem/ HTTP

### Management

SNMP	SNMP v1, SNMP v2c
SNMP MIB	MIB II (RFC1213), Ethernet MIB(RFC3635) Extended Interface MIB(RFC2863 [if X Entry]) Bridge MIB(RFC1493) Dot1q MIB RFC2674, Private MIB Telnet, VT100 (via Console), Web GUI (via HTTP, requires Internet Explorer)
Terminal	

## CentreCOM G900M Series | Layer 2 Gigabit Access Switches

Performance		AT-GS908M	AT-GS916M	AT-GS924M
<b>Switching mode</b>		Store and Forward		
<b>Maximum packet forwarding rate (entire unit/64 Byte)</b>		13.4Mpps	23.8Mpps	35.7Mpps
<b>Switching delay (64 Byte)</b>	1000M <> 1000M	4.0µs	4.2µs	4.0µs
	100M <> 100M	8.8µs	9.3µs	9.0µs
	0M <> 10M	57.3µs	62.8µs	60.9µs
<b>Switching fabric</b>		24Gbps	36Gbps	48Gbps
<b>Memory</b>	Packet Buffer	512KB		
	Flash	16MB		
	Main Memory	64MB		
<b>FDB entry</b>		8K (Maximum)		
<b>Number of VLANs</b>		256 (VID=1 ~ 4,094)		

Power Specifications		AT-GS908M	AT-GS916M	AT-GS924M
<b>Rated input voltage</b>		100–240V AC (10% auto-ranging)		
<b>Rated frequency</b>		50/60Hz		
<b>Rated input current</b>		0.3A	0.5A	0.6A
<b>Maximum input current (actual measured value)</b>		0.2A	0.4A	0.53A
<b>Average power consumption</b>		8.6W (Max 12W)	17W (Max 22W)	25W (Max 30W)

### Environmental Specifications

Operating temperature	0°C to 50°C (32°F to 122°F)
Storage temperature	-20°C to 60°C (-4°F to 140°F)
Operating humidity	5% to 80% (non-condensing)
Storage humidity	5% to 95% (non-condensing)

### Physical Characteristics

Dimensions (W x D x H)

AT-GS908M	26.3 cm × 17.9 cm × 3.8 cm (10.35 in × 7.05 in × 1.5 in)
AT-GS916M	34.1 cm × 21 cm × 4.4 cm (13.42 in × 8.26 in × 1.7 in)
AT-GS924M	44 cm × 21 cm × 4.4 cm (17.32 in × 8.26 in × 1.7 in)

Weight:

AT-GS908M	1.4 kg (3.08 lbs)
AT-GS916M	2.0 kg (4.41 lbs)
AT-GS924M	2.7 kg (5.95 lbs)

### Safety and Electromagnetic Emissions Certifications

EMI	AT-GS908M : VCCI Class B AT-GS916M AT-GS924M : VCCI Class A
Safety Standards	UL60950-1, CSA-C22.2 No. 60950-1
EU RoHS Compliant	

### Package Description

AT-GS9XXM switch  
120V AC power cord  
Management cable (RJ-45 to DB-9)  
Rack-mount kit for AT-GS916M and AT-GS924M  
Install Guide and CLI user's guide available at [alliedtelesis.com](http://alliedtelesis.com)

## Ordering Information

### GS900M Gigabit Copper Switches

#### AT-GS908M-xx

8 × 10/100/1000T ports, 1 × SFP slot  
1 standard AC power supply in a compact form factor

#### AT-GS916M-xx

14 × 10/100/1000T ports, 2 × Combo ports  
(2 × 10/100/1000T or 100FX/1000X ports)  
1 standard AC power supply in a compact form factor

#### AT-GS924M-xx

20 × 10/100/1000T ports, 4 × Combo ports  
(4 × 10/100/1000T or 100FX/1000X ports)  
1 standard AC power supply in a compact form factor

Where xx = 10 for US power cord  
20 for no power cord  
30 for UK power cord  
40 for Australian power cord  
50 for European power cord

### Accessories

#### AT-RKMT-J05

19 in rack-mounting kit for AT-GS908M

### Small Form Pluggable Optics Modules

#### AT-SPSX

SFP, MMF, 1000Mbps, 220 / 500 m, 850 nm, LC

#### AT-SPSX/I

SFP, MMF, 1000Mbps, 220 / 550m, 850 nm, LC  
Extended temperature: -40°C to 85°C

#### AT-SPEX

SFP, MMF, 1000Mbps, 2 km, 1310 nm, LC

#### AT-SPLX10

SFP, SMF, 1000Mbps, 10 km, 1310 nm, LC

#### AT-SPLX10/I

SFP, SMF, 1000Mbps, 10 km, 1310 nm, LC  
Extended temperature: -40°C to 85°C

#### AT-SPLX40

SFP, SMF, 1000Mbps, 40 km, 1310 nm, LC

#### AT-SPZX80

SFP, SMF, 1000Mbps, 80 km, 1550 nm, LC

#### AT-SPBD10-13

SFP, SMF, 1000Mbps, 10 km, 1310/1490 nm, LC-BiDi

#### AT-SPBD10-14

SFP, SMF, 1000Mbps, 10 km, 1490/1310 nm, LC-BiDi

#### AT-SPFX/2

SFP, MMF, 100Mbps, 2 km, 1310 nm, LC

#### AT-SPFXBD-LC-13

SFP, SMF, 100Mbps, 10 km, 1310/1510 nm, LC-BiDi

#### AT-SPFXBD-LC-15

SFP, SMF, 100Mbps, 10 km, 1510/1310 nm, LC-BiDi

#### AT-SPFX/15

SFP, SMF, 100Mbps, 15 km, 1310 nm, LC



NETWORK SMARTER

North America Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

EMEA & CSA Operations | Incheonweg 7 | 1437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

[alliedtelesis.com](http://alliedtelesis.com)

© 2018 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.  
617-000527 Rev G