

AT-WNU300N

Wireless USB Adapter



AT-WNU300N-xx

IEEE 802.11b/g/n 300Mbps high-speed wireless USB adapter

Higher Speed and Longer Reach

The Allied Telesis AT-WNU300N provides desktop PC users or notebook users with access to high-speed wireless networks for flexibility and freedom. You are free to move your PCs within the wireless coverage anywhere you want. Using the latest IEEE 802.11n technology, the wireless connection speed can get up to 300Mbps, more than five times the throughput of the earlier traditional IEEE 802.11g standard. In addition, the wireless range is also extended, ensuring greater connectivity and coverage. Dynamic data rate scaling helps achieve the fastest possible connection within the wireless coverage area.

Supports Latest Applications

The additional performance and throughput delivered by the AT-WNU300N allows users to support the latest applications, such as wireless video streaming, music and video downloads, Internet phone calls, and file sharing.

Security

The security on the AT-WNU300N is backed up by the latest industry compliance WPA and WPA2, and IEEE 802.1x authentications ensure that you get the best security measures possible in the market. It guarantees network access from permitted users only, and gives you a peace of mind that your data will be safe.

Backwards Compatibility and Interoperability

The Allied Telesis AT-WNU300N is backwards compatible with existing wireless standards IEEE 802.11b/g, allowing continued connectivity to existing wireless access points, routers, and client devices. The card is Wi-Fi certified, providing the users with the freedom and confidence when choosing other Wi-Fi certified vendors wireless devices, knowing that these products are interoperable.

Key Features

- High-speed IEEE 802.11n standard delivering data throughput up to 300Mbps
- Backwards compatible with IEEE 802.11b/g standards
- Dynamic data rate scaling ensures maximum network throughput
- Supports wireless data encryption and security via WPA2, WPA and WEP (64/128-bit)
- Supports WMM for wireless QoS on Windows
- Supports Microsoft Windows 2000, XP and Vista O/S
- Support WPS (WiFi Protected Setup) button for easier wireless setting by pushing one button only
- User friendly configuration
- High-speed USB 2.0 interface with data rates up to 12Mbps full speed and 480Mbps high-speed

AT-WNU300N | Wireless USB Adapter

Radio Characteristics

Data Rate With Automatic Fallback

IEEE 802.11n MCS0~15, the maximum 300Mbps data rates (300Mbps Rx PHY rate; 300Mbps Tx PHY support)

IEEE 802.11g 54, 48, 36, 24, 18, 12, 11, 9, 6, and 1Mbps

IEEE 802.11b 11, 5.5, 2, and 1Mbps

Frequency Bands

2.4GHz, actual frequency varies by country

Radio Output Power

11~15 dBm depends on frequencies

IEEE 802.11b 15dBm

IEEE 802.11g 11dBm

IEEE 802.11n 11dBm

Receive sensitivity

IEEE 802.11g 6Mbps: -88dBm
54Mbps: -70dBm

IEEE 802.11n MCS0/7: -82dBm/-64dBm@20MHz
MCS0/7: -79dBm/-61dBm@40MHz
MCS8/15: -79dBm/-61dBm@40MHz

Modulation Schemes

OFDM, BPSK, QPSK, 16-QAM, 64-QAM, DBPSK, DQPSK, CCK

Channels

USA 11

Europe 13

Antenna

Printing antenna

Standards Capability

IEEE 802.11b

IEEE 802.11g

IEEE 802.11n

Security

64/128 bits WEP encryption/decryption with up to four WEP keys

WPA - WPA-EAP (TLS, PEAK, TTLS, EAP-SIM),
WPA-PSK (TKIP), WPA-PSK (AES)

WPA2 - WPA2-EAP (TLS, PEAK, TTLS, EAP-SIM),
WPA2-PSK (TKIP), WPA2-PSK (AES)

IEEE 802.1x authenticator

WPS

Led Status Indicators

Link/Active	On	Radio on
	Blink	Radio on and Tx/Rx data transmission
	Off	Radio off

Driver Support

Windows 2000

Windows XP

Windows Vista

Technical Specifications

Environmental Specifications

Operating temp. 0°C to 45°C

Operating humidity 15% to 95% non-condensing

Storage temp. -10°C to 70°C

Storage humidity 15% to 95% non-condensing

Physical Characteristics

Dimensions 7.75cm x 2.15cm x 1.08cm
(W x D x H) (3.05in x 0.85in x 0.43in)

Weight 0.026 lb (12g)

Electrical/Mechanical/Safety

Approvals

FCC Part 15 Class B

FCC Part 15B, 15C

EN 300 328

EN 301 489-1/-17

EN 61000

EN 55022

EN 50371

C-Tick

AS/NZS 4268

WiFi (b/g/n, WPS)

WHQL

Ordering Information

AT-WNU300N/xx-001

Wireless USB adapter

Where xx = EU for Europe
NA for North America

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2009 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.

617-000349 RevA