

Product	Primary Port	Uplink	Temp Range	PoE Power	No. of PoE-out ports	Alternative mode	Total no. of PoE+ enabled ports (30W)	Total no. of PoE enabled ports (15.4W)	Total no. of PoE enabled ports (7.0W)
<b>CHASSIS-BASED SWITCHES — LAYER 3</b>									
AT-SBx8112	Up to 400 modular	-	0°C to 40°C	1200W or 2400W	240	A	80	155	240
AT-SBx8106	Up to 200 modular	-	0°C to 40°C	1200W or 2400W	120	A	80	120	120
<b>10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 3</b>									
AT-x930-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	48	A	48	48	48
AT-x930-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	24	A	24	24	24
AT-x510-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	48	A	12	24	48
AT-x510-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	24	A	12	24	24
AT-x510L-52GP	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	48	A	6	12	26
AT-x510L-28GP	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	24	A	6	12	24
<b>10/100/1000 MANAGED SWITCHES — LAYER 3</b>									
AT-IE300-12GP <sup>1</sup>	8 x Gigabit Ethernet	4 x Gigabit Ethernet	-40°C to 75°C	240W	8	A	8	8	8
<b>10/100 MANAGED SWITCHES — STACKABLE LAYER 3</b>									
AT-x310-50FP	48 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	48	B	12	24	48
AT-x310-26FP	24 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	24	B	12	24	24
<b>CHASSIS-BASED SWITCHES — LAYER 2</b>									
AT-SBx3112	Up to 400 modular	-	0°C to 40°C	1200W or 2400W	240	A	80	155	240
AT-SBx3106	Up to 200 modular	-	0°C to 40°C	1200W or 2400W	120	A	80	120	120
<b>10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 2</b>									
AT-IX5-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	370W or 720W	24	A	24	24	24
AT-GS948MPX	48 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	48	A	12	24	48
AT-GS924MPX	24 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	24	A	12	24	24
<b>10/100/1000 MANAGED SWITCHES — LAYER 2</b>									
AT-x230-28GP	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	370W	24	A	12	24	24
AT-x230-18GP	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	247W	16	A	8	16	16

<sup>1</sup> IE300-12GP: 4ports High-PoE(60W) is also available

Product	Primary Port	Uplink	Temp Range	PoE Power	No. of PoE-out ports	Alternative mode	Total no. of PoE+ enabled ports (30W)	Total no. of PoE enabled ports (15.4W)	Total no. of PoE enabled ports (7.0W)
<b>10/100/1000 MANAGED SWITCHES — LAYER 2</b>									
AT-x230-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	124W	8	A	4	8	8
AT-GS970M/28PS	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0oC to 50oC	370W	24	A	12	24	24
AT-GS970M/18PS	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0oC to 50oC	247W	16	A	8	16	16
AT-GS970M/10PS	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0oC to 50oC	124W	8	A	4	8	8
AT-IE200-6GP	4 x Gigabit Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	A	4	4	4
<b>10/100 MANAGED SWITCHES — STACKABLE LAYER 2</b>									
AT-FS980M/52PS	48 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 50°C	375W	48	A	12	24	48
AT-FS980M/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 50°C	375W	24	A	12	24	24
<b>10/100 MANAGED SWITCHES — LAYER 2</b>									
AT-FS980M/18PS	16 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	250W	16	A	8	16	16
AT-FS980M/9PS	8 x Fast Ethernet	1 x Gigabit Ethernet	0°C to 50°C	150W	8	A	4	8	8
AT-IE200-6FP	4 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	A	4	4	4
AT-IFS802SP/POE(W)	8 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	123.2W	8	A	-	8	8
<b>10/100/1000 UNMANAGED AND WEBSMART SWITCHES</b>									
AT-GS950/48PS	48 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	370W	24	A	12	24	24
AT-GS950/28PS	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	185W	24	A	4	12	24
AT-GS950/16PS	14 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	185W	16	A	6	12	16
AT-GS950/10PS	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	75W	8	A	2	4	8
AT-GS900/8PS	8 x Gigabit Ethernet	1 x Gigabit Ethernet	0°C to 40°C	75W	4	A	2	4	4
<b>10/100 UNMANAGED AND WEBSMART SWITCHES</b>									
AT-FS750/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 40°C	193W	24	A	4	12	24
AT-FS708LE/POE	8 x Fast Ethernet	-	0°C to 40°C	30W	4	A	-	2	4
AT-FS708/POE	8 x Fast Ethernet	-	0°C to 40°C	65W	8	A	-	4	8
<b>NETWORK INTERFACE CARDS (PCIe)</b>									
AT-2716POE/FXSC	Fast Ethernet	MMF SC	0°C to 40°C	15W	1	A	-	1	1
AT-2716POE/FXST	Fast Ethernet	MMF ST	0°C to 40°C	15W	1	A	-	1	1

Product	Primary Port	Uplink	Temp Range	PoE Power	No. of PoE-out ports	Alternative mode	Total no. of PoE+ enabled ports (30W)	Total no. of PoE enabled ports (15.4W)	Total no. of PoE enabled ports (7.0W)
<b>NETWORK INTERFACE CARDS (PCIe)</b>									
AT-2911GP/LXLC	Gigabit Ethernet	SMF LC	0°C to 40°C	30W	1	A	1	1	1
AT-2911GP/LXSC	Gigabit Ethernet	SMF SC	0°C to 40°C	30W	1	A	1	1	1
AT-2911GP/SFP	Gigabit Ethernet	SFP (FE or Gig)	0°C to 40°C	30W	1	A	1	1	1
AT-2911GP/SXLC	Gigabit Ethernet	MMF LC	0°C to 40°C	30W	1	A	1	1	1
AT-2911GP/SXSC	Gigabit Ethernet	MMF SC	0°C to 40°C	30W	1	A	1	1	1
<b>MEDIA CONVERTERS</b>									
AT-PC200/SC	Fast Ethernet	MMF SC	0°C to 50°C	30W	1	A	1	1	1
AT-PC2000/SC	Gigabit Ethernet	MMF SC	0°C to 50°C	30W	1	A	1	1	1
AT-PC2000/LC	Gigabit Ethernet	MMF LC	0°C to 50°C	30W	1	A	1	1	1
AT-PC2000/SP	Gigabit Ethernet	SFP (FE or Gig)	0°C to 50°C	30W	1	A	1	1	1
AT-IMC1000TP/SFP	Gigabit Ethernet	SFP (FE or Gig)	-40°C to 75°C	30W	1	A	1	1	1
<b>INJECTOR/MIDSPAN</b>									
AT-6101GP	Gigabit Ethernet	-	0°C to 40°C	30W	1	A	1	1	1
AT-6112GP	12 x Gigabit Ethernet	-	0°C to 40°C	370W	12	A	12	12	12