

Product	Primary Port	Uplink	Temp Range	PoE Power	No. of PoE-out ports	Total no. of PoE+ enabled ports (30W)	Total no. of PoE enabled ports (15.4W)	Total no. of PoE enabled ports (7.0W)
<b>CHASSIS-BASED SWITCHES — LAYER 3</b>								
AT-SBx8112	Up to 400 modular	-	0°C to 40°C	1200W or 2400W	240	80	155	240
AT-SBx8106	Up to 200 modular	-	0°C to 40°C	1200W or 2400W	120	80	120	120
<b>10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 3</b>								
AT-x930-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	48	48	48	48
AT-x930-28GPXm	20 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	24	24	24	24
AT-x550-18XSPQm	8 x 1/2.5/5/10G Ethernet 8 x 10G Ethernet	2 x 40G Ethernet	0°C to 45°C	240W	8	8	8	8
AT-x530-28GPX	20 x Gigabit Ethernet 4 x 1/2.5/5 Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	740W	24	24	24	24
AT-x510-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	48	12	24	48
AT-x510-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	24	12	24	24
AT-x510L-52GP	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	48	6	12	26
AT-x510L-28GP	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	24	6	12	24
<b>10/100/1000 MANAGED SWITCHES — LAYER 3</b>								
AT-IE300-12GP <sup>1</sup>	8 x Gigabit Ethernet	4 x Gigabit Ethernet	-40°C to 75°C	240W	8	8	8	8
<b>10/100 MANAGED SWITCHES — STACKABLE LAYER 3</b>								
AT-x310-50FP	48 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	48	12	24	48
AT-x310-26FP	24 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	24	12	24	24
<b>10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 2</b>								
AT-IX5-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	370W or 720W	24	24	24	24
AT-GS948MPX	48 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	48	12	24	48
AT-GS924MPX	24 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	24	12	24	24

<sup>1</sup> IE300-12GP: 4ports High-PoE(60W) is also available

Product	Primary Port	Uplink	Temp Range	PoE Power	No. of PoE-out ports	Total no. of PoE+ enabled ports (30W)	Total no. of PoE enabled ports (15.4W)	Total no. of PoE enabled ports (7.0W)
<b>10/100/1000 MANAGED SWITCHES — LAYER 2</b>								
AT-x230-28GP	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	370W	24	12	24	24
AT-x230-18GP	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	247W	16	8	16	16
AT-x230-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	124W	8	4	8	8
AT-x220-52GP	48 x Gigabit Ethernet	48 x Gigabit Ethernet	0°C to 50°C	740W	48	24	48	48
AT-GS980M/52PS	48 x Gigabit Ethernet	48 x Gigabit Ethernet	0°C to 50°C	740W	48	24	48	48
AT-GS970M/28PS	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	370W	24	12	24	24
AT-GS970M/18PS	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	247W	16	8	16	16
AT-GS970M/10PS	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	124W	8	4	8	8
AT-IE210L-18GP	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 65°C	247W	16	8	16	16
AT-IE210L-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 65°C	124W	8	4	8	8
AT-IE200-6GP	4 x Gigabit Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	4	4	4
AT-IS230-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	8	4	8	8
<b>10/100 MANAGED SWITCHES — STACKABLE LAYER 2</b>								
AT-FS980M/52PS	48 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 50°C	375W	48	12	24	48
AT-FS980M/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 50°C	375W	24	12	24	24
<b>10/100 MANAGED SWITCHES — LAYER 2</b>								
AT-FS980M/18PS	16 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	250W	16	8	16	16
AT-FS980M/9PS	8 x Fast Ethernet	1 x Gigabit Ethernet	0°C to 50°C	150W	8	4	8	8
AT-IE200-6FP	4 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	4	4	4
<b>10/100/1000 UNMANAGED AND WEBSMART SWITCHES</b>								
AT-GS950/48PS	48 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	370W	24	12	24	24
AT-GS950/28PS	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	185W	24	4	12	24
AT-GS950/16PS	14 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	185W	16	6	12	16
AT-GS950/10PS	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	75W	8	2	4	8
AT-GS900/8PS	8 x Gigabit Ethernet	1 x Gigabit Ethernet	0°C to 40°C	75W	4	2	4	4
AT-IS130-6GP	5 x Gigabit Ethernet	1 x Gigabit Ethernet	-40°C to 75°C	90W	4	3	4	4

Product	Primary Port	Uplink	Temp Range	PoE Power	No. of PoE-out ports	Total no. of PoE+ enabled ports (30W)	Total no. of PoE enabled ports (15.4W)	Total no. of PoE enabled ports (7.0W)
<b>10/100 UNMANAGED AND WEBSMART SWITCHES</b>								
AT-FS750/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 40°C	193W	24	4	12	24
AT-FS708/POE	8 x Fast Ethernet	-	0°C to 40°C	30W	4	-	2	4

Media converters, network cards, splitters and injectors are also available from Allied Telesis. Please contact your local sales office for more information or visit our website.

**UK Sales** | Phone: +44 1793 501408 | Email: [UK\\_Sales@Alliedtelesis.com](mailto:UK_Sales@Alliedtelesis.com) | Web: [www.alliedtelesis.com](http://www.alliedtelesis.com)



**NETWORK SMARTER**

**North America Headquarters** | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

**Asia-Pacific Headquarters** | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

**EMEA & CSA Operations** | Incheonweg 7 | 1437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

[alliedtelesis.com](http://alliedtelesis.com)

© 2019 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective ownersR

C618-3410015 RevR