


SwitchBlade x908 Generation 3

High Capacity Stackable Layer 3+ Modular Switch



The Allied Telesis SBx908 GEN3 is the ideal solution for the modern enterprise network core, with connectivity right up to 400G. This stackable modular switch also has the capacity to enable today's Smart City and IoT networks.

The high-capacity 12.8 Terabit fabric eliminates bottlenecks, effortlessly streams video and ensures all traffic in large networks is delivered reliably. Flexible hot-swappable expansion modules (XEMs) support 1/2.5/5/10G, 1/10/25G, 40/100G and 100/400G speeds to easily expand the SBx908 GEN3 to meet network traffic demands, both now and well into the future.

Network automation

Allied Telesis Management Framework™ Plus (AMF Plus) meets the increasing management requirements of modern converged networks, by automating many everyday tasks. AMF Plus has powerful features that allow an entire network to be easily managed as a single virtual device.

Vista Manager™ EX is an intuitive graphical tool for monitoring and managing AMF Plus wired and Autonomous Wave Control (AWC) wireless devices. Full visibility and powerful features enable proactive management of large networks.

Resilient

The convergence of network services in the enterprise has led to increasing demand for highly available networks with minimal downtime.

Allied Telesis Virtual Chassis Stacking (VStack™), in conjunction with link aggregation, provides a network with no single point of failure and a resilient solution for high-availability applications. The SBx908 GEN3 can form a VStack of up to four units, at any port speed, for enhanced resiliency and simplified device management. Stacks can also be created over long distance fiber links, making it the perfect choice for distributed environments too.

Allied Telesis Ethernet Protection Switched Ring (EPSRing™), and the standards-based G.8032 Ethernet Ring Protection, ensure that distributed network segments have high-speed, resilient access to online resources and applications.

Reliable

Designed with reliability in mind, the SBx908 GEN3 guarantees the continual delivery of essential services. Hot-swappable components such as XEMs, fans, and load-sharing Power Supply Units (PSUs) pair with near hitless online stack reconfiguration, to ensure that maintenance doesn't affect network uptime.

Hyper-Converged Infrastructure (HCI)

The SBx908 GEN3 has the performance and resilience to support hyper-converged infrastructure, where servers, storage, and switches connect seamlessly for data-driven environments that are software controlled. This lowers cost and complexity while enabling better scalability and agility in managing and deploying IT services.

Network orchestration

For easy integration into complex networks such as HCI that comprise physical, virtual, and multi-vendor devices, the SBx908 GEN3 features:

- NETCONF/RESTCONF + YANG data modelling for network automation.
- OpenFlow v1.3 for Software Defined Networking (SDN) orchestration.

Reduced operating cost

Energy Efficient Ethernet (EEE), automatically reducing the power consumed by the switch whenever there is no traffic on a port, reducing operating costs.

The SBx908 GEN3 uses the same power supply and fan modules as the GEN2 model, leveraging technology investment.

Key Features

- 12.8 Terabit fabric
- XEMs support 1/2.5/5/10G, 1/10/25G, 40/100G and 100/400G speeds
- Allied Telesis Autonomous Management Framework™ Plus (AMF Plus)
- AMF Security compatible
- Active Fiber Monitoring of fiber data and stacking links
- Large switching and routing tables
- VStack™ up to 4 units, locally or over distance
- EPSRing™ and G.8032 ERPS for resilient rings
- EPSR Master
- Media Redundancy Protocol (MRP)¹
- Media Access Control Security (MACSec)¹
- Multicast Source Discovery Protocol (MSDP)
- Link Monitoring
- Bidirectional Forwarding Detection (BFD)
- Upstream Forwarding Only (UFO)
- VXLAN static tunnels
- AT-Vista Manager mini¹ enables:
 - Wired and wireless network visibility
 - AWC wireless network management
 - AWC-Channel Blanket hybrid wireless
 - AWC-Smart Connect wireless uplinks

- Precision Time Protocol (PTP)¹ Transparent Mode
- NETCONF/RESTCONF with YANG data modelling
- OpenFlow v1.3 for SDN

¹ Available in a future software release

KEY FEATURES

VCStack™

Create a VCStack of up to four units at any port speed. Stacking links are connected in a ring so each device has dual connections to further improve resiliency. VCStack provides a highly available system where network resources are spread out across stacked units, reducing the impact if one of the units fails. Aggregating switch ports on different units across the stack provides excellent network resiliency.

VCStack LD

Long-distance stacking allows a VCStack to be created over fiber links to span longer distances, perfect for a distributed network environment.

Vista Manager mini¹

Integrated into the Device GUI, Vista Manager mini provides full network visibility of AMF Plus wired and AWC wireless devices. Manage and simplify wireless deployment with AWC-Smart Connect, and support optimal wireless performance from AWC hybrid operation with maximum throughput and a seamless Wi-Fi user experience.

Allied Telesis Autonomous Management Framework™ Plus (AMF Plus)

AMF Plus is a sophisticated suite of management tools that provide a simplified approach to network management. Common tasks are automated or made so simple that the everyday running of a network can be achieved without the need for highly-trained, and expensive, network engineers. Powerful features like centralized management, auto-backup, auto-upgrade, auto-provisioning and auto-recovery enable plug-and-play networking and zero-touch management.

The SBx908 GEN3 operating as the AMF Plus master stores firmware and configuration backups for all other network nodes. This enables auto-provisioning and auto-upgrade by providing appropriate files to new network members.

An AMF Plus license provides all standard AMF network management and automation features, and also enables the AMF Plus intent-based networking features in Vista Manager EX.

AMF-Security and Application Proxy

The AMF-Security (AMF-Sec) solution enables internal LAN threat detection and automatic end-point isolation to protect the network. The AMF Application Proxy (included for free in the base license) enables the AMF-Sec controller to communicate with the AMF Plus master when a threat is detected, so the AMF Plus master can take action to block the threat at source by quarantining the infected end-point.

Large Network Tables

High-capacity 12.8 Terabit fabric and 2,800Mpps packet forwarding provide powerful data transfer capability, supporting large campus networks as well as Smart City and IoT solutions. Large MAC and IP host tables are ready for the increasing number of connected devices found in modern enterprise and city-wide networks.

Multi-Speed Ports

Hot-swappable expansion modules (XEMs) support 1/2.5/5/10G, 1/10/25G, 40/100G and 100/400G speeds to easily expand capacity.

Virtual Routing and Forwarding (VRF Lite)

VRF Lite provides Layer 3 network virtualization by dividing a single switch into multiple independent virtual routing domains. With independent routing domains, IP addresses can overlap without causing conflict, allowing multiple customers to have their own secure virtual network within the same physical infrastructure. VRF Lite supports IPv4 and IPv6 unicast and multicast traffic.

The built-in DHCP Server on the SBx908 GEN3 is VRF aware, enabling the supply of IP addresses to clients across multiple isolated networks.

EPSRing™

EPSRing allows several switches to form protected rings with 50ms failover—perfect for high performance at the core of Enterprise or Provider Access networks. The SBx908 GEN3 can act as the EPSR Master..

SuperLoop Protection enables a link between two EPSR nodes to be in separate EPSR domains, improving redundancy and network fault resiliency.

G.8032 Ethernet Ring Protection

G.8032 provides standards-based high-speed ring protection, that can be deployed stand-alone, or interoperate with Allied Telesis EPSR.

Ethernet Connectivity Fault Monitoring (CFM) proactively monitors links and VLANs, and provides alerts when a fault is detected.

sFlow

sFlow is an industry-standard technology for monitoring high-speed switched networks. It provides complete visibility into network use, enabling performance optimization, usage accounting/billing, and defense against security threats. Sampled packets sent to a collector (up to 5 collectors can be configured) ensure it always has a real-time view of network traffic.

Active Fiber Monitoring (AFM)

Active Fiber Monitoring prevents eavesdropping on fiber communications by monitoring received optical power. If an intrusion is detected, the link can be automatically shut down, or an operator alert can be sent. Active Fiber Monitoring is supported on fiber data and fiber stacking links.

TACACS+ Command Authorization

TACACS+ Command Authorization offers centralized control over which commands may be issued by each specific AlliedWare Plus device user. It complements authentication and accounting services for a complete AAA solution.

VLAN Translation

Service Providers can use VLAN Translation to provide customer traffic with a unique VLAN-ID for use within the SP's network. It does this by mapping traffic arriving on a VLAN to a different VLAN on the outgoing paired interface.

This feature is also useful in Enterprise environments where it can be used to merge two networks together, without manually reconfiguring the VLAN numbering scheme.

Media Access Control Security (MACSec)¹

802.1AE MACSec secures all traffic on point-to-point Ethernet links between directly connected nodes, ensuring protection against security threats such as denial of service, intrusion, man-in-the-middle, passive wiretapping, and playback attacks.

Bi-directional Forwarding Detection (BFD)

BFD enables fast detection of link failures, to minimize recovery. It works with static routes, and alongside BGP and OSPF routing protocols supporting faster shutdown of neighbor connections if a peer session goes down. When using VRF-Lite, BFD is supported globally or within a domain.

Upstream Forwarding Only (UFO)

UFO manages which ports in a VLAN can communicate with each other, and which only have upstream access to services, for secure multi-user deployment.

Multicast Source Discovery Protocol (MSDP)

MSDP enables two or more PIM-SM (Sparse Mode) domains to share information on active multicast sources, for more efficient forwarding of multicast traffic.

Precision Time Protocol (PTP)¹

PTP (IEEE 1588v2) synchronizes network clocks with micro-second accuracy, supporting industrial automation and control systems. PTP operates on standalone or stacked switches

Link Monitoring (Linkmon)

Linkmon enables network health monitoring by regularly sending probes over key links to gather metrics comprising latency, jitter, and probe loss. This supports pro-active network management, and can also be used with triggers to automate a change to device or network configuration in response to the declining health of a monitored link.

Virtual Extensible LAN (VXLAN) tunnels

VXLAN tunnels let you join two or more L2 networks over an L3 IP network to form a single L2 broadcast domain. VXLAN adds scalability to cloud computing environments. The SBx908 GEN3 supports static VXLAN tunnels.


NETCONF/RESTCONF

NETCONF/RESTCONF with YANG data modeling provides a standardized way to represent data and securely configure devices, supporting existing management systems.

Software Defined Networking (SDN)

OpenFlow is a key technology for SDN orchestration. SDN controllers and other tools support automated behavior in a network and allow customized applications and services to be run.

Distributed network core



Today's large enterprises demand ready access to online resources and applications, and require a high-performing network that can seamlessly carry multiple converged services. This campus solution uses the SwitchBlade x908 GEN3 and VCStack LD—ideal for a distributed network core that provides high availability, increased capacity and ease of management.

Using VCStack at the core of the network allows multiple switches to appear as a single virtual chassis, simplifying

management. In normal operation, the full bandwidth of the network is used, ensuring always-available online services.

Using Amazon Web Services (AWS) Direct Connect ensures immediate access to cloud-based services, alongside locally stored business data and applications, to fully support modern hybrid-cloud environments.


AMF Plus allows the entire network to be unified for ease of management. The SwitchBlade x908 GEN3 acts as the AMF

Plus Master, automatically backing up the entire network, and enabling plug-and-play networking with zero-touch expansion and recovery

Vista Manager enables visual management and monitoring of the entire network including all wired, wireless, and endpoint devices.

The SwitchBlade x908 GEN3 delivers a protocol-less and Active/Active campus backbone solution, with high performance and flexible scalability.

Smart city network



All over the world, Smart Cities are looking to increase information availability, security and transport efficiency, whilst reducing pollution and waste. Access to real-time data from a variety of sources gives cities the ability to enhance the quality of their urban services, and increase citizen safety.

The SwitchBlade x908 GEN3 is the ideal network core solution for Smart City and IoT networks. Large switching and routing tables support the many devices that make up modern metropolitan networks,


including video surveillance cameras, environmental sensors, information kiosks, public Wi-Fi and many more.

EPSR creates a high-speed resilient ring that can run at up to 400G, and provides extremely fast failover between nodes. EPSR enables rings to recover within as little as 50ms, preventing a node or link failure from impacting the delivery of converged data and video traffic.

AMF plus automates many day-to-day tasks, backs up the entire network, and provides the ability to configure many or all devices city-wide—with a single command.

The SwitchBlade x908 GEN3 and Allied Telesis advanced features support network managers in delivering leading Smart City services.

High performing server connectivity



Today's businesses consume more data than ever, which has become critical to effective operation with always-on access to online resources and applications required. The move to using tools like generative AI and real-time collaboration has lifted the demand for increased performance, and immediate information delivery.

Hyper-Converged Infrastructure (HCI) enables servers, storage, and switches to connect seamlessly in supporting data-driven environments. Centralized SDN management powers hardware and software resources which can be

pooled as required. This lowers cost and complexity while enabling better scalability and agility in managing and deploying IT services.

The SBx908 GEN3 has the switching performance and speed options to support servers delivering business-critical information. The resilient hardware design with dual hot-swappable power supplies and fan modules maximizes connectivity and up-time, while XEM modules, and the ability to stack multiple units provides a scalable and future-proof data delivery solution.

As well as Allied Telesis innovative management tools like AMF Plus and Vista Manager, the SBx908 GEN3 supports industry standard control protocols such as Netconf/Restconf, OpenFlow, and Ansible, so customer-oriented applications and management tools can be easily integrated.

SPECIFICATIONS

Performance

- 12.8 Terabit switching fabric
- 2,800Mpps forwarding rate
- Extensive wirespeed traffic classification for ACLs and QoS
- 10KB L2/L3 Jumbo frames
- Up to 160K MAC address entries
- Up to 96K host entries
- Up to 4K multicast entries (8K available Q4 2025 in AW+ 5.5.5-2)
- Up to 254 Link Aggregation Groups (LAGS) - any combination of static and dynamic (LACP)
- 4K VLANs
- 32GB DDR SDRAM
- 512GB SSD memory
- 24MB packet buffer memory
- Multicore CPU for high performance

Reliability

- Modular AlliedWare Plus operating system
- Dual hot swappable PSUs with 1 + 1 redundancy
- Dual feed support: a separate power circuit can feed each power supply providing extra reliability
- Hot-swappable expansion modules (XEMs)
- Hot-swappable fan modules
- Full environmental monitoring of PSUs, fans, temperature and internal voltages, with SNMP traps to alert network managers in case of any failure

Expandability

- Eight high speed expansion bays supporting a choice of modules for port flexibility and application versatility
- Versatile licensing options for additional features

Power Characteristics

- AC Voltage: 100 to 240V (+/-10% auto ranging)
- Frequency: 47 to 63Hz
- DC Voltage: 36 to 72V

Diagnostic Tools

- Active Fiber Monitoring detects tampering on optical links
- Built-In Self Test (BIST)
- Cable fault locator (TDR)
- Find-me device locator
- Hardware health monitoring
- Automatic link flap detection and port shutdown
- Optical Digital Diagnostic Monitoring (DDM)
- Ping polling for IPv4 and IPv6
- Port mirroring
 - No limit on mirrored ports
 - Up to 4 mirror (analyzer) ports
- VLAN mirroring (RSPAN)
- TraceRoute for IPv4 and IPv6
- Uni-Directional Link Detection (UDLD)

IPv4 Features

- Black hole routing
- Directed broadcast forwarding
- DNS relay
- Equal Cost Multi Path (ECMP) routing

- Policy-based routing
- Route maps
- Route redistribution (OSPF, BGP, RIP)
- Static unicast and multicast routing for IPv4
- UDP broadcast helper (IP helper)
- Up to 600 Virtual Routing and Forwarding (VRF lite) domains (with license)

IPv6 Features

- DHCPv6 client and relay
- DNSv6 client and relay
- IPv4 and IPv6 dual stack
- IPv6 hardware ACLs
- Device management over IPv6 networks with SNMPv6, Telnetv6 and SSHv6
- NTPv6 client and server
- Static unicast and multicast routing for IPv6
- Log to IPv6 hosts with Syslog v6
- IPv6 Ready certified
- VRF Lite

Management

- 7-segment LED provides at-a-glance status and fault information
- Allied Telesis Management Framework Plus (AMF Plus) enables powerful centralized management and zero-touch device installation and recovery
- Try AMF Plus for free with the built-in Starter license (includes network management and automation features, but not Vista Manager AMF Plus features)
- NETCONF/RESTCONF northbound interface with YANG data modelling
- Console management port on the front panel for ease of access
- Eco-friendly mode allows ports and LEDs to be disabled to save power
- Industry-standard CLI with context-sensitive help
- Out-of-band 10/100/1000T Ethernet management port
- Powerful CLI scripting engine
- Comprehensive SNMP MIB support for standards-based device management
- Built-in text editor
- Event-based triggers allow user-defined scripts to be executed upon selected system events
- USB interface allows software release files, configurations and other files to be stored for backup and distribution to other devices

Quality of Service

- 8 priority queues with a hierarchy of high priority queues for real time traffic, and mixed scheduling, for each switch port
- Bandwidth limiting (virtual bandwidth). Limit bandwidth per port or per traffic class down to 64kbps
- Wirespeed traffic classification with low latency essential for VoIP and real-time streaming media applications
- IPv6 QoS support and IPv6-aware storm protection
- Policy-based QoS based on VLAN, port, MAC and general packet classifiers
- Policy-based storm protection
- Extensive remarking capabilities and taildrop for queue congestion control
- Queue scheduling options for strict priority, weighted round robin or mixed scheduling

- IP precedence and DiffServ marking based on layer 2, 3 and 4 headers

Resiliency Features

- Control Plane Prioritization (CPP) ensures the CPU always has sufficient bandwidth to process network control traffic
- Dynamic link failover (host attach)
- Ethernet Protection Switched Rings (EPSR) with SuperLoop Protection (SLP) and EPSR enhanced recovery for extra resiliency
- G.8032 Ethernet Ring Protection
- Media Redundancy Protocol (MRP)1
- Bidirectional Forwarding Detection (BFD)
- Flexi-stacking allows the use of any port speed to stack
- Long-Distance VSTACK over fiber (VSTACK LD)
- Loop protection: loop detection and thrash limiting
- PVST+ compatibility mode
- STP root guard
- VSTACK fast failover minimizes network disruption

Security

- Access Control Lists (ACLs) based on layer 3 and 4 headers
- Configurable ACLs for management traffic
- Dynamic ACLs assigned via port authentication
- ACL Groups enable multiple hosts/ports to be included in a single ACL, reducing configuration
- Auth fail and guest VLANs
- Authentication, Authorisation and Accounting (AAA)
- Bootloader can be password protected for device security¹
- BPDU protection
- DHCP snooping, IP source guard and Dynamic ARP Inspection (DAI)
- DoS attack blocking and virus throttling¹
- Dynamic VLAN assignment
- MAC address filtering and MAC address lock-down
- Media Access Control Security (MACSec)¹
- Network Access and Control (NAC) features manage endpoint security
- Learn limits (intrusion detection) for single ports or LAGs
- Private VLANs provide security and port isolation for multiple customers using the same VLAN
- Secure Copy (SCP)
- Secure File Transfer Protocol (SFTP) client
- Strong password security and encryption
- TACACS+ command authorisation
- Tri-authentication: MAC-based, web-based and IEEE 802.1x
- Web-based authentication
- RADIUS group selection per VLAN or port
- RADIUS Proxy

Software-Defined Networking (SDN)

- OpenFlow v1.3 with support for encryption, connection interruption and inactivity probe

Environmental Specifications

- Operating temperature range:
0°C to 50°C (32°F to 122°F)
Derated by 1°C per 305 meters (1,000 ft)

¹ Available in a future software release

- Storage temperature range:
-25°C to 70°C (-13°F to 158°F)

■ Operating relative humidity range:
5% to 90% non-condensing

■ Storage relative humidity range:
5% to 95% non-condensing

■ Operating altitude:
3,050 meters maximum (10,000 ft)
- Immunity: EN55035, EN61000-3-levels 2
(Harmonics), and 3 (Flicker)
- Safety

■ Standards: UL 62368-1 3rd Edition, AS/NZS
62368-1, CSA C22.2 No. 62368-1:19 3rd Edition, EN
IEC 62368-1:2020+A11, EN 60825-1:2014/A11:2021

■ Certification: UL-US, UL-CA

- Restrictions on Hazardous Substances
(RoHS) Compliance
- EU RoHS compliant

■ China RoHS compliant

- Electrical Approvals and Compliances
- EMC: EN55032 class A, FCC class A, VCCI class A

Physical Specifications

	Width	Depth	Height	Mounting	Weight
SwitchBlade x908 GEN3	440 mm (17.32 in)	480 mm (18.89 in)	132 mm (5.19 in)	Rack-mount 3 RU	15.81 kg (34.85 lb)
SBxPWRSYS2	84 mm (3.30 in)	170 mm (6.69 in)	40 mm (1.57 in)	N/A	1.9 kg (4.18 lb)
XEM3-12XTm (1/2.2/5/10G)	130 mm (5.11 in)	166 mm (6.53 in)	40 mm (1.57 in)	N/A	0.70 kg (1.54 lb)
XEM3-12YS (1/10/25G)	130 mm (5.11 in)	166 mm (6.53 in)	40 mm (1.57 in)	N/A	0.76 kg (1.68 lb)
XEM3-8CQ (40/100G)	130 mm (5.11 in)	166 mm (6.53 in)	40 mm (1.57 in)	N/A	0.82 kg (1.81 lb)
XEM3-2DQ (100/400G)	130 mm (5.11 in)	166 mm (6.53 in)	40 mm (1.57 in)	N/A	0.70 kg (1.54 lb)

Power Consumption

	Max Power Consumption	Max Heat Dissipation
SBx908 GEN3 with 8 x XEM3-12XTm	750W	2559 BTU/h
SBx908 GEN3 with 8 x XEM3-12XYS	710W	2423 BTU/h
SBx908 GEN3 with 8 x XEM3-8CQ	1130W	3856 BTU/h
SBx908 GEN3 with 8 x XEM3-2DQ	840W	2866 BTU/h

Latency (microseconds)

	Latency
XEM3-12XTm	3.13µs
XEM3-12XYS	3.13µs
XEM3-8CQ	2.1µs
XEM3-2DQ	1.73µs

STANDARDS & PROTOCOLS

AlliedWare Plus Operating System

Version 5.5.5-1

Authentication

- RFC 1321

MD5 Message-Digest algorithm
- RFC 1828

IP authentication using keyed MD5

Border Gateway Protocol (BGP)

- BGP

dynamic capability
- BGP

outbound route filtering
- RFC 1772

Application of the Border Gateway Protocol (BGP) in the Internet
- RFC 1997

BGP communities' attribute
- RFC 2439

BGP route flap damping
- RFC 2545

Use of BGP-4 multiprotocol extensions for IPv6 inter-domain routing
- RFC 2918

Route refresh capability for BGP-4
- RFC 3882

Configuring BGP to block Denial-of-Service (DoS) attacks
- RFC 4271

Border Gateway Protocol 4 (BGP-4)
- RFC 4360

BGP extended communities
- RFC 4456

BGP route reflection - an alternative to full mesh iBGP
- RFC 4724

BGP graceful restart
- RFC 4760

Multiprotocol Extensions for BGP-4
- RFC 5065

Autonomous system confederations for BGP
- RFC 5492

Capabilities Advertisement with BGP-4
- RFC 5925

The TCP Authentication Option

- RFC 6793

BGP Support for Four-Octet Autonomous System (AS) Number Space
- RFC 7606

Revised Error Handling for BGP UPDATE Messages

Cryptographic Algorithms

- FIPS Approved Algorithms
- Encryption (Block Ciphers):
- AES (ECB, CBC, CFB and OFB Modes)

3DES (ECB, CBC, CFB and OFB Modes)
- Block Cipher Modes:
- CCM

CMAC

GCM

XTS
- Digital Signatures & Asymmetric Key Generation:
- DSA

ECDSA

RSA
- Secure Hashing:
- SHA-1

SHA-2 (SHA-224, SHA-256, SHA-384, SHA-512)
- Message Authentication:
- HMAC (SHA-1, SHA-2(224, 256, 384, 512)
- Random Number Generation:
- DRBG (Hash, HMAC and Counter)
- Non FIPS Approved Algorithms
- RNG (AES128/192/256)

DES

MD5

Ethernet

- IEEE 802.1AE Media Access Control Security(MACSec)
- IEEE 802.2 Logical Link Control (LLC)
- IEEE 802.3 Ethernet
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3ae 10Gigabit Ethernet
- IEEE 802.3an 10GBASE-T
- IEEE 802.3az Energy Efficient Ethernet (EEE)
- IEEE 802.3ba 40GBASE-X
- IEEE 802.3bj 100GBASE-X
- IEEE 802.3bs 400GBASE-X
- IEEE 802.3by 25GBASE-X
- IEEE 802.3u 100BASE-X
- IEEE 802.3x Flow control - full-duplex operation
- IEEE 802.3z 1000BASE-X

IPv4 Features

- RFC 768

User Datagram Protocol (UDP)
- RFC 791

Internet Protocol (IP)
- RFC 792

Internet Control Message Protocol (ICMP)
- RFC 793

Transmission Control Protocol (TCP)
- RFC 826

Address Resolution Protocol (ARP)
- RFC 894

Standard for the transmission of IP datagrams over Ethernet networks
- RFC 919

Broadcasting Internet datagrams
- RFC 922

Broadcasting Internet datagrams in the presence of subnets
- RFC 932

Subnetwork addressing scheme
- RFC 950

Internet standard subnetting procedure
- RFC 951

Bootstrap Protocol (BootP)
- RFC 1027

Proxy ARP

RFC 1035	DNS client
RFC 1042	Standard for the transmission of IP datagrams over IEEE 802 networks
RFC 1071	Computing the Internet checksum
RFC 1122	Internet host requirements
RFC 1191	Path MTU discovery
RFC 1256	ICMP router discovery messages
RFC 1518	An architecture for IP address allocation with CIDR
RFC 1519	Classless Inter-Domain Routing (CIDR)
RFC 1542	Clarifications and extensions for BootP
RFC 1591	Domain Name System (DNS)
RFC 1812	Requirements for IPv4 routers
RFC 1918	IP addressing
RFC 2581	TCP congestion control

IPv6 Features

RFC 1981	Path MTU discovery for IPv6
RFC 2460	IPv6 specification
RFC 2464	Transmission of IPv6 packets over Ethernet networks
RFC 3484	Default address selection for IPv6
RFC 3587	IPv6 global unicast address format
RFC 3596	DNS extensions to support IPv6
RFC 4007	IPv6 scoped address architecture
RFC 4193	Unique local IPv6 unicast addresses
RFC 4213	Transition mechanisms for IPv6 hosts and routers
RFC 4291	IPv6 addressing architecture
RFC 4443	Internet Control Message Protocol (ICMPv6)
RFC 4861	Neighbor discovery for IPv6
RFC 4862	IPv6 Stateless Address Auto-Configuration (SLAAC)
RFC 5014	IPv6 socket API for source address selection
RFC 5095	Deprecation of type 0 routing headers in IPv6
RFC 5175	IPv6 Router Advertisement (RA) flags option
RFC 6105	IPv6 Router Advertisement (RA) guard

Management

AT Enterprise MIB including AMF Plus MIB and traps	
Optical DDM MIB	
SNMPv1, v2c and v3	
ANSI/TIA-1057 Link Layer Discovery Protocol-Media Endpoint Discovery (LLDP-MED)	
IEEE 802.1AB Link Layer Discovery Protocol (LLDP)	
RFC 1155	Structure and identification of management information for TCP/IP-based Internets
RFC 1157	Simple Network Management Protocol (SNMP)
RFC 1212	Concise MIB definitions
RFC 1213	MIB for network management of TCP/IP-based Internets: MIB-II
RFC 1215	Convention for defining traps for use with the SNMP
RFC 1227	SNMP MUX protocol and MIB
RFC 1239	Standard MIB
RFC 1724	RIPv2 MIB extension
RFC 2011	SNMPv2 MIB for IP using SMIv2
RFC 2012	SNMPv2 MIB for TCP using SMIv2
RFC 2013	SNMPv2 MIB for UDP using SMIv2
RFC 2578	Structure of Management Information v2 (SMIv2)
RFC 2579	Textual conventions for SMIv2
RFC 2580	Conformance statements for SMIv2
RFC 2674	Definitions of managed objects for bridges with traffic classes, multicast filtering and VLAN extensions
RFC 2741	Agent extensibility (AgentX) protocol
RFC 2819	RMON MIB (groups 1,2,3 and 9)
RFC 2863	Interfaces group MIB
RFC 3176	sFlow: a method for monitoring traffic in switched and routed networks
RFC 3411	An architecture for describing SNMP management frameworks
RFC 3412	Message processing and dispatching for the SNMP
RFC 3413	SNMP applications
RFC 3414	User-based Security Model (USM) for SNMPv3
RFC 3415	View-based Access Control Model (VACM) for SNMP
RFC 3416	Version 2 of the protocol operations for the SNMP
RFC 3417	Transport mappings for the SNMP
RFC 3418	MIB for SNMP
RFC 3621	Power over Ethernet (PoE) MIB

RFC 3635	Definitions of managed objects for the Ethernet-like interface types
RFC 3636	IEEE 802.3 MAU MIB
RFC 4022	MIB for the Transmission Control Protocol TCP)
RFC 4113	MIB for the User Datagram Protocol (UDP)
RFC 4188	Definitions of managed objects for bridges
RFC 4292	IP forwarding table MIB
RFC 4293	MIB for the Internet Protocol (IP)
RFC 4318	Definitions of managed objects for bridges with RSTP
RFC 4560	Definitions of managed objects for remote ping, traceroute and lookup operations
RFC 5424	The Syslog protocol
RFC 6020	YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)
RFC 6241	Network Configuration Protocol (NETCONF)
RFC 6244	Architecture for Network Management Using NETCONF and YANG
RFC 6527	Definitions of managed objects for VRRPv3
RFC 7950	The YANG 1.1 Data Modeling Language
RFC 8040	RESTCONF Protocol

Multicasting Features

Bootstrap Router (BSR) mechanism for PIM-SM	
IGMP query solicitation	
IGMP snooping (IGMPv1, v2 and v3)	
IGMP snooping fast-leave	
IGMP/MLD multicast forwarding (IGMP/MLD proxy)	
MLD snooping (MLDv1 and v2)	
PIM-SM and SSM for IPv6	
RFC 2236	Internet Group Management Protocol v2 (IGMPv2)
RFC 2710	Multicast Listener Discovery (MLD) for IPv6
RFC 2715	Interoperability rules for multicast routing protocols
RFC 3306	Unicast-prefix-based IPv6 multicast addresses
RFC 3376	IGMPv3
RFC 3590	Source Address Selection for the Multicast Listener Discovery (MLD) Protocol
RFC 3810	Multicast Listener Discovery v2 (MLDv2) for IPv6
RFC 3956	Embedding the Rendezvous Point (RP) address in an IPv6 multicast address
RFC 3973	PIM Dense Mode (DM)
RFC 4541	IGMP and MLD snooping switches
RFC 4604	Using IGMPv3 and MLDv2 for source-specific multicast
RFC 4607	Source-specific multicast for IP
RFC 7761	Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol specification

Open Shortest Path First (OSPF)

OSPF link-local signaling	
OSPF MD5 authentication	
OSPF restart signaling	
Out-of-band LSDB resync	
RFC 1245	OSPF protocol analysis
RFC 1246	Experience with the OSPF protocol
RFC 1370	Applicability statement for OSPF
RFC 1765	OSPF database overflow
RFC 2328	OSPFv2
RFC 2370	OSPF opaque LSA option
RFC 2740	OSPFv3 for IPv6
RFC 3101	OSPF Not-So-Stubby Area (NSSA) option
RFC 3509	Alternative implementations of OSPF area border routers
RFC 3623	Graceful OSPF restart
RFC 3630	Traffic engineering extensions to OSPF
RFC 4552	Authentication/confidentiality for OSPFv3
RFC 5329	Traffic engineering extensions to OSPFv3
RFC 5340	OSPFv3 for IPv6 (partial support)

Quality of Service Features

IEEE 802.1p	Priority tagging
RFC 2211	Specification of the controlled-load network element service
RFC 2474	DiffServ precedence for eight queues/port
RFC 2475	DiffServ architecture
RFC 2597	DiffServ Assured Forwarding (AF)
RFC 2697	A single-rate three-color marker
RFC 2698	A two-rate three-color marker
RFC 3246	DiffServ Expedited Forwarding (EF)

¹ Available in a future software release

Resiliency Features

IEC61439-2	Media Redundancy Protocol (MRP) ¹
IEEE 802.3ad	Static and dynamic link aggregation
EEE 802.1ag	CFM Continuity Check Protocol (CCP)
IEEE 802.1AX	Link aggregation (static and LACP)
IEEE 802.1D	MAC bridges
IEEE 802.1s	Multiple Spanning Tree Protocol (MSTP)
IEEE 802.1w	Rapid Spanning Tree Protocol (RSTP)
ITU-T G.8032 / Y.1344	Ethernet Ring Protection Switching (ERPS)
RFC 5798	Virtual Router Redundancy Protocol version 3 (VRRPv3) for IPv4 and IPv6
RFC5880	Bidirectional Forwarding Detection (BFD)

Routing Information Protocol (RIP)

RFC 1058	Routing Information Protocol (RIP)
RFC 2080	RIPng for IPv6
RFC 2081	RIPng protocol applicability statement
RFC 2082	RIP-2 MD5 authentication
RFC 2453	RIPv2

Security Features

SSH remote login	
SSLv2 and SSLv3	
TACACS+ Accounting, Authentication, Authorization (AAA)	
IEEE 802.1AE	MAC Security (MACsec) ¹
IEEE 802.1X	Authentication protocols (TLS, TTLS, PEAP and MD5)
IEEE 802.1X	Multi-suplicant authentication
IEEE 802.1X	Port-based network access control
RFC 2818	HTTP over TLS ("HTTPS")
RFC 2865	RADIUS authentication
RFC 2866	RADIUS accounting
RFC 2868	RADIUS attributes for tunnel protocol support
RFC 2986	PKCS #10: certification request syntax specification v1.7
RFC 3579	RADIUS support for Extensible Authentication Protocol (EAP)
RFC 3580	IEEE 802.1x RADIUS usage guidelines
RFC 3748	Extensible Authentication Protocol (EAP)
RFC 4251	Secure Shell (SSHv2) protocol architecture
RFC 4252	Secure Shell (SSHv2) authentication protocol
RFC 4253	Secure Shell (SSHv2) transport layer protocol
RFC 4254	Secure Shell (SSHv2) connection protocol
RFC 5176	RADIUS CoA (Change of Authorization)
RFC 5246	Transport Layer Security (TLS) v1.2
RFC 5280	X.509 certificate and Certificate Revocation List (CRL) profile
RFC 5425	Transport Layer Security (TLS) transport mapping for Syslog
RFC 5656	Elliptic curve algorithm integration for SSH
RFC 6125	Domain-based application service identity within PKI using X.509 certificates with TLS
RFC 6614	Transport Layer Security (TLS) encryption for RADIUS
RFC 6668	SHA-2 data integrity verification for SSH

Services

RFC 854	Telnet protocol specification
RFC 855	Telnet option specifications
RFC 857	Telnet echo option
RFC 858	Telnet suppress go ahead option
RFC 1091	Telnet terminal-type option
RFC 1350	The TFTP protocol (revision 2)
RFC 1985	SMTP service extension
RFC 2049	MIME
RFC 2131	DHCPv4 (server, relay and client)
RFC 2132	DHCP options and BootP vendor extensions
RFC 2616	Hypertext Transfer Protocol - HTTP/1.1
RFC 2821	Simple Mail Transfer Protocol (SMTP)
RFC 2822	Internet message format
RFC 3046	DHCP relay agent information option (DHCP option 82)
RFC 3315	Dynamic Host Configuration Protocol for IPv6 (DHCPv6)
RFC 3396	Encoding Long Options in the Dynamic Host Configuration Protocol (DHCPv4)
RFC 3633	IPv6 prefix options for DHCPv6
RFC 3646	DNS configuration options for DHCPv6
RFC 3993	Subscriber-ID sub-option for DHCP relay agent option

VLAN Support

Generic VLAN Registration Protocol (GVRP)
IEEE 802.1ad Provider bridges (VLAN stacking, Q-in-Q)
IEEE 802.1Q Virtual LAN (VLAN) bridges
IEEE 802.1v VLAN classification by protocol and port
IEEE 802.3ac VLAN tagging
Static VXLAN tunnels (part of RFC 7348)

Feature Licenses

	Description	Includes	Stack Licensing
AT-FL-GEN3-01	SwitchBlade x908 GEN3 Premium license	<ul style="list-style-type: none"> ■ OSPF² (16,000 routes) ■ BGP4² (5,000 routes) ■ PIMv4-SM, DM and SSM (2,000 entries) ■ VLAN double tagging (Q-in-Q) ■ RIPng (5,000 routes) ■ OSPFv3 (8,000 routes) ■ BGP4+ (5,000 routes) ■ MLDv1 and v2 ■ PIMv6-SM and SSM (1,000 entries) ■ VRF lite (63 domains) ■ RADIUS Full ■ UDLD ■ VLAN Translation ■ G.8032 ring protection ■ Ethernet CFM ■ VXLAN ■ PTP Transparent Mode¹ 	■ One license per stack member
AT-SW-APM10-1YR^{3,4}	Cumulative AMF Plus Master license	■ AMF Plus Master license for up to 10 nodes for 1 year	■ One license per stack
AT-SW-APM10-5YR^{3,4}	Cumulative AMF Plus Master license	■ AMF Plus Master license for up to 10 nodes for 5 years	■ One license per stack
AT-SW-APC10-1YR^{3,5}	Cumulative AMF Plus Controller license	■ AMF Plus Controller license for up to 10 areas for 1 year	■ One license per stack
AT-SW-APC10-5YR^{3,5}	Cumulative AMF Plus Controller license	■ AMF Plus Controller license for up to 10 areas for 5 years	■ One license per stack
AT-FL-GEN3-OF13-1YR	OpenFlow license	■ OpenFlow v1.3 for 1 year	■ Not supported on a stack
AT-FL-GEN3-OF13-5YR	OpenFlow license	■ OpenFlow v1.3 for 5 years	■ Not supported on a stack
AT-FL-GEN3-MSEC¹	MACSec license	■ Media Access Control Security	■ One license per stack member
AT-FL-GEN3-VLF¹	VRF-Lite Full license	■ VRF lite (600 domains)	■ One license per stack member
AT-SW-AWC10-1YR⁶	Cumulative AWC license	■ Autonomous Wave Control (AWC) license for up to 10 access points for 1 year	■ One license per stack
AT-SW-AWC10-5YR⁶	Cumulative AWC license	■ Autonomous Wave Control (AWC) license for up to 10 access points for 5 years	■ One license per stack
AT-SW-CB10-1YR-2022⁷	Cumulative AWC-CB and AWC-SC license	■ AWC Channel Blanket and AWC Smart Connect license for up to 10 access points for 1 year	■ One license per stack
AT-SW-CB10-5YR-2022⁷	Cumulative AWC-CB and AWC-SC license	■ AWC Channel Blanket and AWC Smart Connect license for up to 10 access points for 5 years	■ One license per stack

¹ Available in a future software release

² 64 OSPF and BGP routes included in base license

³ From AW+ version 5.5.2-2 onwards, AMF Plus licenses provide all standard AMF network management and automation features. They also enable the AMF Plus intent-based networking features in Vista Manager EX (from version 3.10.1 onwards)

⁴ Purchase one license per 10 nodes (up to 300 nodes maximum)

⁵ Purchase one license per 10 areas (up to 60 areas maximum)

⁶ 5 APs can be managed for free. Purchase one license per 10 additional APs (up to 300 APs maximum)

⁷ Channel Blanket and Smart Connect are not available as free services. Both an AWC-CB license and an AWC license are required for Channel Blanket and/or Smart Connect to operate. Purchase one AWC-CB license per 10 APs (up to 300 APs maximum).

ORDERING INFORMATION

AT-SBx908GEN3-BOy⁸	High capacity Layer 3+ modular switch chassis with 8 x high speed expansion bays, fans included
AT-SBxPWRSYS2-Bxy^{9,10}	Hot-swappable load-sharing power supply
AT-FAN08¹⁰	Spare hot-swappable fan module
AT-XEM3-12XTm	12 x 1/2.5/5/10G RJ45 ports
AT-XEM3-12YS	12 x 1/10/25G SFP28 ports
AT-XEM32-8CQ	8 x 40/100G QSFP28 ports
AT-XEM3-2DQ	2 x 100/400G QSFP56-DD ports
AT-VT-Kit3	Management cable (USB to serial console)

⁸ Where Oy = 01 for 1 year Net Cover support
05 for 5 years Net Cover support

¹⁰ Note that fans are included but NO power supplies ship with the base chassis, they must be ordered separately

⁹ Where x =
1y for AC power supply with US power cord
2y for AC power supply with no power cord
3y for AC power supply with UK power cord
4y for AC power supply with AU power cord
5y for AC power supply with EU power cord

Accessories

400G QSFP55-DD Modules	
AT-QSFPDD-SR8	400G, QSFPDD, MPO, 850 nm short-haul up to 100 m with MMF
AT-QSFPDD-2.5CU	2.5m, QSFPDD28, 400G, direct attach cable
100G QSFP28 Modules	
AT-QSFP28-SR4	100GSR 850nm short-haul up to 100 m with MMF
AT-QSFP28-LR4	100GLR 1310nm medium-haul, 10 km with SMF
AT-QSFP28-1CU	1 meter QSFP28 direct attach cable
AT-QSFP28-3CU	3 meter QSFP28 direct attach cable
40G QSFP+ Modules	
AT-QSFPSR4	40GSR4 850 nm short-haul up to 150 m with MMF, MPO-12
AT-QSFPSR4LCa	40GSR4 850 nm short-haul up to 150 m with MMF, LC
AT-QSFPLR4	40GLR4 1310 nm medium-haul, 10 km with SMF
AT-QSFPER4	40GER4 1310 nm long-haul, 40 km with SMF
AT-MTP12-1	1 meter MTP optical cable for AT-QSFPSR
AT-MTP12-5	5 meter MTP optical cable for AT-QSFPSR
AT-QSFP1CU	1 meter QSFP+ direct attach cable
AT-QSFP3CU	3 meter QSFP+ direct attach cable

25G SFP28 Modules	
AT-SP25SR/I	100 m, 25G SFP, LC, MMF, 850 nm, industrial temperature, TAA ¹¹
AT-SP25LR/I	10 km, 25G SFP, LC, SMF, 1310 nm, industrial temperature, TAA ¹¹
AT-SP25TW1	1 m, 25G SFP, direct attach cable
AT-SP25TW3	3 m, 25G SFP, direct attach cable
10GbE SFP+ Modules	
AT-SP10SR	10GSR 850 nm short-haul, 300 m with MMF
AT-SP10SR/I	10GSR 850 nm short-haul, 300 m with MMF industrial temperature
AT-SP10LRM	10GLRM 1310 nm short-haul, 220 m with MMF
AT-SP10LR	10GLR 1310 nm medium-haul, 10 km with SMF
AT-SP10LRa/I	10GLR 1310 nm medium-haul, 10 km with SMF industrial temperature
AT-SP10ER20/I	10GER 1310nm long-haul, 20 km with SMF industrial temperature
AT-SP10ER40/I	10GER 1310nm long-haul, 40 km with SMF industrial temperature
AT-SP10ZR80/I	10GER 1550nm long-haul, 80 km with SMF industrial temperature
AT-SP10TM	1G/2.5G/5G/10G, 100m copper, TAA ¹¹
10GbE SFP+ Cables	
AT-SP10TW1	1 meter SFP+ direct attach cable
AT-SP10TW3	3 meter SFP+ direct attach cable
AT-SP10TW7	7 meter SFP+ direct attach cable

1G SFP Modules	
AT-SPTX	10/100/1000T 100 m copper
AT-SPSX	1000SX GbE multi-mode 850 nm fiber up to 550 m
AT-SPSX/I	1000SX GbE multi-mode 850 nm fiber up to 550 m industrial temperature
AT-SPEX	1000X GbE multi-mode 1310 nm fiber up to 2 km
AT-SPLX10a	1000LX SFP, LC, SMF, 1310 nm (10 km), TAA ¹¹
AT-SPLX10/I	1000LX GbE single-mode 1310 nm fiber up to 10 km industrial temperature
AT-SPBD10-13	1000LX GbE Bi-Di (1310 nm Tx, 1490 nm Rx) fiber up to 10 km
AT-SPBD10-14	1000LX GbE Bi-Di (1490 nm Tx, 1310 nm Rx) fiber up to 10 km
AT-SPLX40	1000LX GbE single-mode 1310 nm fiber up to 40 km
AT-SPZX80	1000ZX GbE single-mode 1550 nm fiber up to 80 km

¹¹ Trade Act Agreement compliant